

Amendments to the Specification

Please amend paragraphs 0021, 0028, and 0030 of the subject application as follows:

[0021] Referring more particularly to the drawings, a signal light 50 for a chair 52 with a back 54 and a seat 56 and positioned at a gaming table 58 is illustrated in FIGS. 1 and 2. In a number of embodiments, the signal light 50 includes a light housing 60 and a switch housing 62. In other embodiments, the light housing 60 may include a power supply 64. The light housing 60 is disposed or mounted on a support 66 which is mounted to the chair 52 such that the light housing 60 is elevated above the chair 52 as particularly shown in FIG. 2. The switch housing 62 is operatively connected to the light housing 60 such that the switch housing 62 is spatially separated the light housing 60. This spatial separation of the housings 60 and 62 is indicated by alpha A in FIGS. 2 and 3. In a number of embodiments, the light housing 60 may include a plurality of differently colored lights that a casino may designate for respective services when lit, which will be discussed in more detail below. In still other embodiments, the switch housing 62 may be moved and positioned with respect to the light housing 60.

[0028] In some of the embodiments, the pivoting mechanism 84 may include ~~be a~~ an indexed elbow hinge that enables the support 66 to be adjusted at discrete positions. Alternatively, the mounting elements 80 and 82 may provide for continuous adjustment. In still other embodiments such as that shown in FIG. 9, the support 66 is not rigid by may include an alligator-neck section 86 that enables positioning of the support 66 while retaining the support 66 in a desired position.

[0030] With reference to FIG. 10, a mounting structure 92 may be provided in some of the embodiments for mounting the battery housing 68 to the chair 52. The mounting structure 92 may include a bracket 94 that may be mounted on the top of the back 54 of the chair 52 with a clamp 96. The mounting structure ~~90~~ 92 may include a strap 98 connected between the bracket 94 and the battery housing 68 so that the battery housing 68 is suspended at the rear of the chair 52.